

Date of revision 07/22/2019

Page n. 1/14

## PU300 part B

# **Safety Data Sheet**

According to U.S.A. Federal Hazcom 2012

## 1. Identification

1.1. Product identifier

ADES / PU300N Code: Product name PU300 part B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Catalyst for epoxy-polyurethanic systems

1.3. Details of the supplier of the safety data sheet

Mondo S.p.A. Name

Full address Piazzale E. Stroppiana, 1 District and Country

12051 Alba (CN)

Italia

tel. 0039/0173/232111 fax 0039/0173/232400

e-mail address of the competent person info@mondoita.com

1.4. Emergency telephone number

Mondo S.p.A. tel. 0039/0173/232111 For urgent inquiries refer to

### 2. Hazards identification

## 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement

Hazard pictograms:

Harmful if swallowed. Acute toxicity, category 4 Acute toxicity, category 4 Harmful in contact with skin.

Skin corrosion, category 1 Causes severe skin

burns and eye damage.

Serious eye damage, category 1 Causes serious eye

damage.

Skin sensitization, category 1

May cause an allergic

skin reaction.



Date of revision 07/22/2019

## PU300 part B

Page n. 2/14





Signal words: Danger

Hazard statements:

H302+H312 Harmful if swallowed or in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.

Precautionary statements:

Prevention:

**P260** Do not breathe dust / fume / gas / mist / vapours / spray.

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

**P270** Do not eat, drink or smoke when using this product.

**P264** Wash hands thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

Response:

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.

P310 Immediately call a POISON CENTER / doctor

P304+P340 IF INHALED: remove person to fresh air and keep comfortable for breathing.

P330 Rinse mouth.

P302+P352 IF ON SKIN: wash with plenty of water

P362+P364 Take off contaminated clothing and wash it before reuse.

P301+P312 IF SWALLOWED: Call a POISON CENTER / doctor / if you feel unwell.

**P363** Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents / container

The mixture contains 30.00 % of components of unknown acute dermal toxicity.

.....

#### 2.2. Other hazards

Environmental classification as for Reg. (EU) 1272/2008 (CLP):

The product is classified as hazardous for environment pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

Classification and Hazard Statement

Hazardous to the aquatic environment, chronic toxicity, category 3 Harmful to aquatic life with long lasting effects.

Hazard statements:

**H412** Harmful to aquatic life with long lasting effects.



Date of revision 07/22/2019

# PU300 part B

Page n. 3/14

Precautionary statements:

Prevention:

**P273** Avoid release to the environment.

Response:

|--

Storage:

Disposal: **P501** 

P501 Dispose of contents / container

Additional hazards

Information not available

# 3. Composition/information on ingredients

#### 3.1. Substances

Information not relevant

#### 3.2. Mixtures

Contains:

Identification	Conc. %	Classification:
3-AMINOMETHYL 3,5,5- TRIMETHYLCYCLOHEXYLAMINE CAS 2855-13-2	60	Acute toxicity, category 4 H302, Acute toxicity, category 4 H312, Skin corrosion, category 1B H314, Serious eye damage, category 1 H318, Skin sensitization, category 1 H317, Hazardous to the aquatic environment, chronic toxicity, category 3 H412
EC 220-666-8		official toxicity, category 3 11412
INDEX 612-067-00-9		
2,4,6- TRIS(DIMETHYLAMINOMETHYL) PHENOL		
CAS 90-72-2	20	Acute toxicity, category 4 H302, Eye irritation, category 2 H319, Skin irritation, category 2 H315
EC 202-013-9		
INDEX 603-069-00-0		
Styrenated phenol		
CAS 61788-44-1	10	Acute toxicity, category 4 H302, Eye irritation, category 2B H320, Skin irritation, category 2 H315, Hazardous to the aquatic environment, chronic toxicity, category 2 H411
EC 262-975-0		toxicity, category 2 11411
INDEX -		
BENZYL ALCOHOL		
CAS 100-51-6	10	Acute toxicity, category 4 H302, Acute toxicity, category 4 H332
EC 202-859-9		
INDEX 603-057-00-5		

The full wording of hazard (H) phrases is given in section 16 of the sheet.



Date of revision 07/22/2019

## PU300 part B

Page n. 4/14

#### 4. First-aid measures

#### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## 5. Fire-fighting measures

#### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

## 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

#### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire-fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

#### 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions



Date of revision 07/22/2019

## PU300 part B

Page n. 5/14

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## 7. Handling and storage

#### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Information not available

### 8. Exposure controls/personal protection

#### 8.1. Control parameters

Information not available

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

#### HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

## SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

### EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

### RESPIRATORY PROTECTION



Date of revision 07/22/2019

PU300 part B

Page n. 6/14

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

#### **ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

## 9. Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Appearance liquid Colour yellow Odour ammonia Odour threshold N.A.  $11.5 \div 12.5$ 10 °C Melting point / freezing point Initial boiling point N.A. Boiling range N.A. Flash point 115 °C Evaporation rate N.A. Flammability of solids and gases N.A. Lower inflammability limit N.A. Upper inflammability limit N.A. Lower explosive limit N.A. Upper explosive limit N.A. Vapour pressure 0.02 hPa Vapour density N.A.

Relative density 0.95 g/cm<sup>3</sup> (23 °C)

Solubility N.A.
Partition coefficient: n-octanol/water N.A.
Auto-ignition temperature N.A.
Decomposition temperature N.A.

Viscosity 5 ÷ 20 mPa s (23 °C)

Explosive properties N.A. Oxidising properties N.A.

#### 9.2. Other information

Information not available

## 10. Stability and reactivity

#### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

BENZYL ALCOHOL

Decomposes at temperatures above 870°C/1598°F.Possibility of explosion.



Date of revision 07/22/2019

## PU300 part B

Page n. 7/14

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE

May react dangerously with: strong oxidising agents, concentrated inorganic acids.

BENZYL ALCOHOL

May react dangerously with: hydrobromic acid, iron,oxidising agents, sulphuric acid. Risk of explosion on contact with: phosphorus trichloride.

#### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

3-AMINOMETHYL 3,5,5-TRIMETHYLCYCLOHEXYLAMINE

Avoid contact with: strong acids, strong oxidants.

BENZYL ALCOHOL

Avoid exposure to: air, sources of heat, naked flames.

#### 10.5. Incompatible materials

BENZYL ALCOHOL

Incompatible with: sulphuric acid, oxidising substances, aluminium.

## 10.6. Hazardous decomposition products

Information not available

## 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.



Date of revision 07/22/2019

## PU300 part B

Page n. 8/14

### 11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

BENZYL ALCOHOL

LD50 (Oral) 1230 mg/kg Rat

LD50 (Dermal) 2000 mg/kg Rabbit

LC50 (Inhalation) > 4.1 mg/l/4h Rat

## SKIN CORROSION / IRRITATION

Corrosive for the skin

## SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

### RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

## GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

## REPRODUCTIVE TOXICITY



Date of revision 07/22/2019

## PU300 part B

Page n. 9/14

Does not meet the classification criteria for this hazard class

### STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

#### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

#### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

## 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

### 12.1. Toxicity

Information not available

### 12.2. Persistence and degradability

BENZYL ALCOHOL

Rapidly degradable

2,4,6-TRIS(DIMETHYLAMINOMETHYL)

PHENOL

Solubility in water > 10000 mg/l

NOT rapidly degradable

3-AMINOMETHYL 3,5,5-

TRIMETHYLCYCLOHEXYLAMINE

Solubility in water 1000 - 10000 mg/l

NOT rapidly degradable

#### 12.3. Bioaccumulative potential

BENZYL ALCOHOL

Partition coefficient: n-octanol/water 1.1

2,4,6-TRIS(DIMETHYLAMINOMETHYL)

PHENOL

Partition coefficient: n-octanol/water -0.66

12.4. Mobility in soil

Information not available.



Date of revision 07/22/2019

## Page n. 10/14

## PU300 part B

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1 %.

#### 12.6. Other adverse effects

Information not available

## 13. Disposal considerations

#### 13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## 14. Transport information

#### 14.1. UN number

ADR / RID, IMDG, 2735

IATA:

### 14.2. UN proper shipping name

ADR / RID: AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. IMDG: AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S.

### 14.3. Transport hazard class(es)

ADR / RID: Class: 8 Label: 8

IMDG: Class: 8 Label: 8

IATA: Class: 8 Label: 8



## 14.4. Packing group

ADR / RID, IMDG, III IATA:

## 14.5. Environmental hazards

ADR / RID: NO
IMDG: NO
IATA: NO



Date of revision 07/22/2019

# PU300 part B

Page n. 11/14

14.6. Special	precautions	for user
---------------	-------------	----------

ADR / RID: HIN - Kemler: 80 Limited Quantities: 5 Tunnel restriction code: (E)

Special Provision: -

IMDG: EMS: F-A, S-B Limited Quantities: 5

IATA: Cargo: Maximum quantity: 60 L Packaging instructions:

856 Maximum Packaging quantity: 5 L

instructions: 852

Special Instructions:

Pass.:

A3, A803

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

## 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal Regulations

TSCA:

All components are listed on TSCA Inventory.

Clean Air Act Section 112(b):

No component(s) listed.

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act – Priority Pollutants:

No component(s) listed.

Clean Water Act – Toxic Pollutants:

No component(s) listed.



Date of revision 07/22/2019

# PU300 part B

Page n. 12/14

DEA List I Chemicals (Precursor Chemicals):	
No component(s) listed.	
DEA List II Chemicals (Essential Chemicals):	
No component(s) listed.	
EPA List of Lists:	
313 Category Code:	
No component(s) listed.	
EPCRA 302 EHS TPQ:	
No component(s) listed.	
EPCRA 304 EHS RQ:	
No component(s) listed.	
CERCLA RQ:	
No component(s) listed.	
EPCRA 313 TRI:	
No component(s) listed.	
RCRA Code:	
No component(s) listed.	
CAA 112 (r) RMP TQ:	
No component(s) listed.	
State Regulations	
Massachussetts:	
100-51-6	BENZYL ALCOHOL
Minnesota:	
100-51-6	BENZYL ALCOHOL
New Jersey:	
2855-13-2	3-AMINOMETHYL 3,5,5- TRIMETHYLCYCLOHEXYLAMINE
New York:	



Date of revision 07/22/2019

## PU300 part B

Page n. 13/14

No component(s) listed.

Pennsylvania:

100-51-6 BENZYL ALCOHOL

California:

90-72-2

TRIS(DIMETHYLAMINOMETHYL)

PHENOL (Phenols)

Proposition 65:

International Regulations

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Candadian WHMIS

Information not available

### 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H302 Harmful if swallowed.

H302+H312 Harmful if swallowed or in contact with skin.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H320 Cause eye irritation. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

## LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code ADR: European Agreement concerning the carriage of Dangerous goods by Road



Date of revision 07/22/2019

## PU300 part B

Page n. 14/14

- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal Dose 50%
- N.A.: not available
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

#### GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh Registry of Toxic Effects of Chemical Substances
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Comunication Standard (HCS 2012)
- IARC website
- List of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachussetts 105 CMR Department of public health 670.000: "Right to Know"
- Minensota Chapter 5206 Departemnt Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

This revision supersedes any previous edition.